MSDS Format : ANSI						
PDF Copy Print E-mail						
CORNING • INNO	ATIONS FOR LIVIN	G™				
	Personal Protective Equipment	Pictograms	DOTPictograms	-		
	♥ &	Controlled	Not Regulated	_		
	Protective Safety Gloves Glasses			-		
SECTION 1 - PRO	DUCT AND COMPA	NY IDENTIFICATION				
Due du et Ne re e c	BlackChu			NFPA		
Product Name: Synonyms:	BlackSky Acoustic insula	tion - board				
Manufacturer Name		Acoustic insulation - board Owens Corning Insulating Systems, LLC				
Address:	One Owens Co	One Owens Corning Parkway Toledo, OH 43659				
Customer Service P Number:	Customer Service Phone 1-800-GET-PINK or 1-800-438-7465 Number:					
Health Issues Information:		1-800-GET-PINK or 1-800-438-7465				
Technical Product Information:	nformation:			HMIS Health Hazard 1		
Emergency Phone Number:	Phone 1-419-248-5330 (after 5pm ET and weekends)			Fire Hazard 0		
CHEMTREC:		(24 hours everyday)		Reactivity 0		
Website:		www.owenscorning.com Personal Protection X				
MSDS Creation Date: March 11, 2013						

# SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name		CAS#	Ingredient Percent	EC Num.
Fiber Glass (continuous filament, respirable)	non-	65997-17-3	75 - 85 by weight	266-046-0
Cured Binder		N/A	4 - 7 by weight	
Hydrocarbon Polymers			0 - 1 by weight	
	Contir mecha small	anufactured co nuous filamen anically proces amount of res	0 - 1 by weight ntinuous filament glass fibers are non- t glass products that are chopped, crus ised during manufacturing or use may spirable particulate, some of which may 8 for Exposure Limit Data.	hed or severely contain a very
	small disclo	enough quan sure. These co	ponents of this product are non-hazard tity as to not meet regulatory threshold omponents contain no substances or in classification of this product.	is for

# SECTION 3 - HAZARDS IDENTIFICATION

#### Applies to Product

No unusual conditions are expected from this product under normal conditions of use. Emergency Overview:

Route of Exposure:

BlackSky

Revision::

Eye contact Skin contact Inhalation

Potential Health Effects:

Eye:	May cause slight irritation.
Skin:	May cause slight skin irritation.
Inhalation:	May cause irritation of respiratory tract.
Ingestion:	Ingestion of this product is unlikely.
Chronic Health Effects:	There is no known chronic health effect connected with long-term use or contact with this product.
Carcinogenicity:	This material is not considered a carcinogen.
Potential Environmental Effects :	There is no known ecological information for this material.
Aggravation of Pre-Existing Conditions:	Chronic respiratory or skin conditions may temporarily worsen from exposure to this product.
OSHA Regulatory Status:	This product is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

# SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Do not rub or scratch eyes. If eye irritation persists, consult a specialist.
Skin Contact:	Wash off immediately with soap and cold water. DO NOT use warm water because this will open up the pores of the skin, which will cause further penetration of the fibers. Use a wash cloth to help remove fibers. DO NOT rub or scratch affected areas. Remove contaminated clothing. If irritation persists get medical attention.
Inhalation:	Move to fresh air. If symptoms persist, call a physician.
Ingestion:	Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. Rinse mouth with water and drink water to remove fibers from the throat. If symptoms persist, call a physician.
Note to Physicians:	Treat symptomatically.

# SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:	Non Flammable.
Flash Point:	None.
Flash Point Method:	Not applicable.
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
Extinguishing Media:	dry chemical foam carbon dioxide (CO2) water fog
Protective Equipment:	Wear self-contained breathing apparatus (SCBA) and full fire fighting protective gear.
Unusual Fire Hazards:	Hydrogen chloride to be released from the PVC barrier and vinyl facings during a fire.
Hazardous Combustion Byproducts:	Carbon monoxide. Carbon dioxide. hydrogen. Other undetermined compounds could be released in small quantities.
Universal Fire And Explosion Hazards:	Not available.

## NFPA Ratings:

NFPA Health:	1
NFPA Flammability:	0
NFPA Reactivity:	0

# SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Avoid contact with skin and eyes.
Environmental Precautions:	Prevent further leakage or spillage if safe to do so.
BlackSky Revision::	Owens Corning Insulating Systems, LLC

Methods for containment:	This material will settle out of the air. Prevent from spreading by covering, diking or other means.
Methods for cleanup:	Use an industrial vacuum cleaner with a high efficiency filter to clean up dust and fiber contamination. Avoid dry sweeping. Pick up and transfer to properly labeled containers.
Other Precautions:	Does not apply.

## SECTION 7 - HANDLING and STORAGE

Handling:	Avoid dust formation. Do not breathe dust. Wear personal protective equipment.
Storage:	Keep product in its packaging until use to minimize potential dust generation. Product should be kept dry and undercover.
Hygiene Practices:	Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use.

# SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Provide local exhaust and/or general ventilation to maintain exposure below regulatory and recommended limits. Dust collection system must be used in transferring operations, cutting or machining or other dust generating processes, such as using power tools. Vacuum or wet clean-up methods should be used.
Eye/Face Protection:	Safety glasses with side-shields.
Skin Protection Description:	Protective gloves. Long sleeved shirt and long pants.
Respiratory Protection:	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended. Consult your company's procedures for selection, training, inspection and maintenance of respirators or consult the NIOSH web site (http://www.cdc.gov/niosh/npptl/topics/respirators/disp_part) for a list of dust respirator types and approved suppliers.
General Hygiene Considerations:	Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use.

## EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline ACGIH	Quebec Canada	Ontario Canada	Mexico
Fiber Glass (continuous filament, non- respirable)	PEL-TWA: 1 f/cc (Respirable)	TLV-TWA: 1 f/cc (Respirable) 5 mg/m3 (inhalable particles)		TWAEV: 1 f/cc (Respirable) 5 mg/m3 (Inhalable)	TWA: 10 mg/m3
Aluminum oxide	PEL-TWA: 15 mg/m3 as Aluminum oxide (Total particulate/dust) PEL-TWA: 5 mg/m3 as Aluminum oxide (Respirable)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 (Total particulate/dust)	TWAEV-TWA: 10 mg/m3 (Total particulate/dust)	VEMP-TWA: 10 mg/m3 (Total particulate/dust)

# SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State:	Solid, Board, Pellets
Physical State Appearance:	Fibrous board
Color:	Black.
Odor:	organic
Boiling Point:	Not applicable.
Melting Point:	No Data
Specific Gravity:	No Data
Solubility:	Insoluble in water.
Vapor Density:	No Data
Vapor Pressure:	No Data
Evaporation Rate:	No Data
pH:	No Data
Viscosity:	Not applicable.
Flash Point:	None.

## SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal conditions.
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	None expected
Incompatible Materials:	No materials to be especially mentioned.
Special Decomposition Products:	See Section 5 of MSDS for hazardous decomposition products during a fire.

## SECTION 11 - TOXICOLOGICAL INFORMATION

#### Applies to Product :

Acute Toxicity:

Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. High exposures may cause difficulty breathing, congestion, and chest tightness.

Carcinogens:							
	ACGIH	NIOSH	OSHA	IARC	NTP	Canada	MEXICO
Fiber Glass (continuous filament, non- respirable)	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	Group 3 - Not Classifiable as to its Carcinogenicity to Humans.	No Data		No Data
Cured Binder	No Data	No Data	No Data	No Data	No Data		No Data
Aluminum oxide	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	No Data	No Data		A4 Not Classifiable as a Human Carcinogen

#### Applies to Product :

Sensitization:	No information available.
Mutagenicity:	No information available.
Reproductive Toxicity:	No information available.
Teratogenicity:	No information available.
Neurological Effects:	No information available.
Cured Binder :	
Ingestion:	Ingestion - Rat LD50: 7 gm/kg - [Autonomic Nervous System - Other (direct) parasympathomimetic Behavioral - Muscle weakness Lungs, Thorax, or Respiration - Respiratory depression](RTECS)
Aluminum oxide :	
Inhalation:	Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death](RTECS)

## SECTION 12 - ECOLOGICAL INFORMATION

Applies to Product :	
Ecotoxicity:	This material is not expected to cause harm to animals, plants or fish.
Bioaccumulation:	Not available.
Biodegradation:	Not available.
Mobility In Environmental Media:	Not available.

#### SECTION 13 - DISPOSAL CONSIDERATIONS

Applies to Product :	
Waste Disposal:	Dispose of in accordance with Local, State, Federal and Provincial regulations.
Contaminated Packaging:	Empty containers should be taken for local recycling, recovery or waste disposal.
RCRA Number:	No EPA Waste Numbers are applicable for this product's components.
RCRA Characteristics:	This material is not expected to be a characteristic hazardous waste under RCRA.

BlackSky Revision::

# SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name:	Not Regulated.
IATA Shipping Name:	Not Regulated.
Canadian Shipping Name:	Not Regulated.
IMDG Shipping Name :	Not Regulated.
ADR Shipping Name :	Not Regulated.
RID Shipping Name :	Not Regulated.
ICAO Shipping Name:	Not Regulated.
MEX Shipping Name :	Not Regulated.

## SECTION 15 - REGULATORY INFORMATION

# Inventory Status

	Japan ENCS	EINECS	Philippines	China	South Korea
		Number	PICCS		KECL
Fiber Glass (continuous filament, non-	Not listed	266-046-0	Listed	Listed	KE-17630
respirable)					
Cured Binder	Not listed			Listed	KE-35185
Aluminum oxide	(1) -23	215-691-6	Listed		KE-01012

	Australia AICS	Canada DSL	TSCA Inventory	
			Status	
Fiber Glass (continuous filament, non- respirable)	Listed	Listed	Listed	
Cured Binder	Listed	Listed	Listed	
Aluminum oxide	Listed	Listed	Listed	

#### Applies to Product :

Canada Reg. Status:	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.			
Canada WHMIS:	Not controlled.			
CA PROP 65:	The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This product does not contain any Proposition 65 chemicals.			
SARA:	This product does not contain any chem reporting requirements of the Superfund Reauthorization Act of 1986 (SARA) Title	d Amendments and		
Section 311/312 Hazard				
Categories:	Acute Health Hazard: Chronic Health Hazard: Risk of ignition: Sudden Release of Pressure Hazard: Reactive Hazard:	Yes No No No		
Clean Air Act:	This product does not contain any Haza	rdous Air Pollutants (HAPs).		
<u>Aluminum oxide</u> :				
Canada IDL:	Identified under the Canadian Hazardou Disclosure List: 1%. Item: 50(1298) Ite			
Section 313:	Listed			

### Fiber Glass (continuous filament, non-respirable) :

EC Number:	266-046-0
Aluminum oxide :	
EC Number:	215-691-6

## State Right To Know

	RI	MN	IL	PA	МА
Fiber Glass (continuous filament, non-	No Data	Listed	No Data	No Data	No Data
respirable)					
Cured Binder	No Data				
Aluminum oxide	Listed	Listed	No Data	Listed	Listed

	IJ		
Fiber Glass (continuous filament, non-	No Data		
respirable)			
Cured Binder	No Data		
Aluminum oxide	Listed		

# SECTION 16 - ADDITIONAL INFORMATION HMIS Health Hazard: 1 HMIS Fire Hazard: 0 HMIS Reactivity: 0 HMIS Personal Protection: X MSDS Creation Date: March 11, 2013 MSDS Author: HAR

 ${\tt Copyright} \circledast$  1996-2011 Actio Corporation. All Rights Reserved.